

RAITA

STAGES FOR ALL NEEDS

tp // 16.9.2018

BELLOW STAGE

The movable bellow stage can be easily opened out in a desired location and, once the event is over, can be moved back into storage.

Bellow stages are telescopically retractable. The manually-operated stage is opened out by pulling manually and retracted by turning a crank handle. The electrically-powered stage is driven by pressing buttons on the end of a mobile cable.

The movable manually-operated stage can be stored in a normal equipment storeroom, for example. The electrically-powered stage is not movable. It is advisable to create a recess for it in the wall, into which it can be driven after use.

The visible surfaces of bellow stages are varnished birch plywood.

Accessories: set of wheel transfer equipment, loose steps, side railings, curtain system and corner padding as collision protection when the stage is retracted.



BELLOW STAGE



Standard sizes and recommend operation

Standard height is 600 mm, storage height 1050 mm.
Pay attention, the additional depth of 400mm must be added when electrically driven bellow stage is in use

| D | W | H | Closed | Operation | Movable |
|------|------|-----|--------|-----------|---------|
| 3200 | 2975 | 600 | 920 | manual | yes |
| 3200 | 4000 | 600 | 920 | manual | yes |
| 3200 | 4750 | 600 | 920 | manual | yes |
| 3200 | 5950 | 600 | 920 | manual | yes |
| 4000 | 2975 | 600 | 920 | manual | yes |
| 4000 | 4000 | 600 | 920 | manual | yes |
| 4000 | 4750 | 600 | 920 | manual | yes |
| 4000 | 5950 | 600 | 920 | manual | yes |
| 4800 | 4000 | 600 | 1100 | manual | yes |
| 4800 | 4750 | 600 | 1100 | manual | yes |
| 4800 | 5950 | 600 | 1100 | manual | no |
| 4800 | 7125 | 600 | 1100 | manual | no |
| 5600 | 4000 | 600 | 1300 | manual | yes |
| 5600 | 4750 | 600 | 1300 | electric | no |
| 5600 | 5950 | 600 | 1300 | electric | no |
| 5600 | 7125 | 600 | 1300 | electric | no |
| 6400 | 4750 | 600 | 1500 | electric | no |
| 6400 | 5950 | 600 | 1500 | electric | no |
| 6400 | 7125 | 600 | 1500 | electric | no |
| 7200 | 5950 | 600 | 1700 | electric | no |
| 7200 | 7125 | 600 | 1700 | electric | no |
| 7200 | 7950 | 600 | 1700 | electric | no |
| 7200 | 8350 | 600 | 1700 | electric | no |
| 7200 | 8925 | 600 | 1700 | electric | no |
| 7200 | 9500 | 600 | 1700 | electric | no |
| 8000 | 7125 | 600 | 1900 | electric | no |
| 8000 | 7950 | 600 | 1900 | electric | no |
| 8000 | 8325 | 600 | 1900 | electric | no |
| 8000 | 8925 | 600 | 1900 | electric | no |
| 8000 | 9500 | 600 | 1900 | electric | no |



GLOBE STAGE

The multipurpose modular Globe Stage is suitable for both indoor and outdoor use. The size of one module is 100 x 200 cm and the height 20,30, 40,60cm 80 and 100 cm depending on choice. The stage can withstand a load of 750 kg/m².

Its frame is made of aluminium profile. The deck material is plywood colour dark brown

Accessories: stairs, railings, curtains to protect the base.

CURTAIN SYSTEMS

We make two kinds of curtain systems: collapsible and rotatable.

The collapsible curtain system is suitable for use with the movable bellow stage. After use, the frame structures and curtains can be detached and stored in the storage stands included in the delivery.

The rotatable curtain system operates with the bellows stage installed in a fixed location. The structures of the system are rotated after use against the wall with the curtains.



For BELLOW STAGE

CUSTOMERS

Sport Arenas

Multipurpose
halls

Teathers

Schools

RAITA

RAITA

Thank you !

www.raitaseating.com

Tuomo Ponto

myyntipäällikkö / Sales Manager

Raita Katsomot Oy / Raita Seating Ltd

Ylivieskantie 186, FI86300 OULAINEN

m: +358 40 175 7200

tuomo.ponto@raitasport.com